


Метчики машинные Paradur® H



- HSS-E
- форма заборного конуса С (2-3 нитки)
- для обработки материалов твердостью 200-1000 Н/мм² (32 HRC), дающих сливную и сегментную стружку

NPT


ASME B1.20.1
1:16

	P	M	K	N	S	H	O
Без покрытия			●	●●			●

PWZ-Norm	D _N Nom	нитек на дюйм	l ₁ js16 мм	L _c мм	d ₁ h9 мм	□ h12 мм	l _g мм	N	Без покрытия
									Обозначение 25167
	1/16-27	27	80	14	8	6,2	9	3	-NPT1/16
	1/8-27	27	90	14	11	9	12	3	-NPT1/8
	1/4-18	18	100	20	14	11	14	3	-NPT1/4
	3/8-18	18	110	20	16	12	15	4	-NPT3/8
	1/2-14	14	125	26	18	14,5	17	4	-NPT1/2
	3/4-14	14	140	26	22	18	21	5	-NPT3/4
	1-11 1/2	11,5	150	31	28	22	25	5	-NPT1
	1 1/4-11 1/2	11,5	160	31	32	24	27	5	-NPT1.1/4
	1 1/2-11 1/2	11,5	160	31	36	29	32	6	-NPT1.1/2
	2-11 1/2	11,5	180	31	45	35	38	7	-NPT2



Метчики машинные Paradur® N



- HSS-E
- форма заборного конуса С (2-3 нитки)
- угол подъема винтовой канавки 15°
- для обработки материалов твердостью 200-1000 Н/мм² (32 HRC), дающих сливную стружку

NPT


ASME B1.20.1
1:16

	P	M	K	N	S	H	O
var	●●		●●	●●			

PWZ-Norm	D _N Nom	нитек на дюйм	l ₁ js16 мм	L _c мм	d ₁ h9 мм	□ h12 мм	l _g мм	N	VAP
									Обозначение 25460
	1/16-27	27	80	14	8	6,2	9	3	-NPT1/16
	1/8-27	27	90	14	11	9	12	3	-NPT1/8
	1/4-18	18	100	20	14	11	14	3	-NPT1/4
	3/8-18	18	110	20	16	12	15	4	-NPT3/8
	1/2-14	14	125	26	18	14,5	17	4	-NPT1/2
	3/4-14	14	140	26	22	18	21	5	-NPT3/4
	1-11 1/2	11,5	150	31	28	22	25	5	-NPT1



Метчики машинные Paradur® NI



- HSS-E
- форма заборного конуса С (2-3 нитки)
- угол подъёма винтовой канавки 15°
- для обработки материалов твердостью 700-1400 Н/мм² (44 HRC), дающих сливную стружку

NPT


ASME B1.20.1
1:16

	P	M	K	N	S	H	O
Без покрытия	●				●●		

PWZ-Norm	D _N Nom	нитек на дюйм	l ₁ js16 мм	L _c мм	d ₁ h9 мм	□ h12 мм	l _g мм	N	Без покрытия
									Обозначение 25467
	1/16-27	27	80	14	8	6,2	9	3	-NPT1/16
	1/8-27	27	90	14	11	9	12	4	-NPT1/8
	1/4-18	18	100	20	14	11	14	4	-NPT1/4
	3/8-18	18	110	20	16	12	15	5	-NPT3/8
	1/2-14	14	125	26	18	14,5	17	5	-NPT1/2
	3/4-14	14	140	26	22	18	21	5	-NPT3/4
	1-11 1/2	11,5	150	31	28	22	25	5	-NPT1



Метчики машинные Paradur Inox® 40




- HSS-E
- форма заборного конуса С (2-3 нитки)
- угол подъёма винтовой канавки 40°
- для обработки материалов твердостью 350-1200 Н/мм² (36 HRC), дающих сливную стружку

NPT

ASME B1.20.1
1:16

	P	M	K	N	S	H	O
Без покрытия	●	●	●	●			


PWZ-Norm



D _N Nom	нитек на дюйм	l ₁ js16 мм	L _c мм	d ₁ h9 мм	□ h12 мм	l _g мм	N	Без покрытия Обозначение 255630
1/8-27	27	90	14	11	9	12	3	-NPT1/8
1/4-18	18	100	20	14	11	14	3	-NPT1/4
3/8-18	18	110	20	16	12	15	4	-NPT3/8
1/2-14	14	125	26	18	14,5	17	4	-NPT1/2



Метчики машинные Paradur Inox®



- HSS-E
- форма заборного конуса С (2-3 нитки)
- угол подъёма винтовой канавки 30°
- для обработки материалов твердостью 350-1200 Н/мм² (36 HRC), дающих сливную стружку

NPT

ASME B1.20.1
1:16

	P	M	K	N	S	H	O
var	●	●	●	●	●	●	●
THL	●	●	●	●	●	●	●

PWZ-Norm	D _N Nom	нитек на дюйм	l ₁ js16 мм	L _c мм	d ₁ h9 мм	□ h12 мм	l _g мм	N	VAP	THL
									Обозначение 25567	Обозначение 2556702
	1/16-27	27	80	14	8	6,2	9	3	-NPT1/16	
	1/8-27	27	90	14	11	9	12	4	-NPT1/8	-NPT1/8
	1/4-18	18	100	20	14	11	14	4	-NPT1/4	-NPT1/4
	3/8-18	18	110	20	16	12	15	5	-NPT3/8	-NPT3/8
	1/2-14	14	125	26	18	14,5	17	5	-NPT1/2	-NPT1/2
	3/4-14	14	140	26	22	18	21	5	-NPT3/4	
	1-11 1/2	11,5	150	31	28	22	25	5	-NPT1	

