


# Раскатники машинные Protodyn® S Plus



$\leq 3,5 \times D_N$



- HSS-E
- форма заборного конуса C (2-3,5 нитки)
- для обработки материалов твердостью 200-1200 Н/мм<sup>2</sup> (36 HRC), дающих сливную стружку

## UNC

ASME B1.1

	P	M	K	N	S	H	O
TiN	●●	●●	●●	●●	●		

DIN 2184-1 2BX	$D_N$ -P Nom	$D_N$ мм	$l_1$ js16 мм	$L_c$ мм	$l_3$ $\pm 1$ мм	$d_1$ h9 мм	$\square$ h12 мм	$l_g$ мм	TiN Обозначение DP2261705
	2-56	2,184	45	7	12	2,8	2,1	5	-UNC2
	4-40	2,845	56	9	18	3,5	2,7	6	-UNC4
	6-32	3,505	56	11	20	4	3	6	-UNC6
	8-32	4,166	63	12	21	4,5	3,4	6	-UNC8
	10-24	4,826	70	13	25	6	4,9	8	-UNC10
	1/4-20	6,35	80	15	30	7	5,5	8	-UNC1/4
	5/16-18	7,938	90	18	35	8	6,2	9	-UNC5/16
	3/8-16	9,525	100	20	39	10	8	11	-UNC3/8

DIN 2184-1 2BX	$D_N$ -P Nom	$D_N$ мм	$l_1$ js16 мм	$L_c$ мм	$l_3$ $\pm 1$ мм	$d_1$ h9 мм	$\square$ h12 мм	$l_g$ мм	TiN Обозначение DP2266705
	7/16-14	11,113	100	20	-	8	6,2	9	-UNC7/16
	1/2-13	12,7	110	23	-	9	7	10	-UNC1/2
	5/8-11	15,875	110	25	-	12	9	12	-UNC5/8

