


Раскатники машинные Protodyn® S Plus


 $\leq 3,5 \times D_N$


- HSS-E
- форма заборного конуса C (2-3,5 нитки)
- для обработки материалов твердостью 200-1200 Н/мм² (36 HRC), дающих сливную стружку

UNF

ASME B1.1

| | | | | | | | |
|-----|----|----|---|----|---|---|---|
| | P | M | K | N | S | H | O |
| TiN | ●● | ●● | ● | ●● | ● | | |

| DIN 2184-1 2BX | D_N -P Nom | D_N мм | l_1 js16 мм | L_c мм | l_3 ± 1 мм | d_1 h9 мм | \square h12 мм | l_g мм | TiN Обозначение DP2361705 |
|----------------|-----------------|-------------|---------------------|-------------|------------------------|-------------------|------------------------|-------------|---------------------------------|
| | 2-64 | 2,184 | 45 | 7 | 12 | 2,8 | 2,1 | 5 | -UNF2 |
| | 4-48 | 2,845 | 56 | 9 | 18 | 3,5 | 2,7 | 6 | -UNF4 |
| | 6-40 | 3,505 | 56 | 11 | 20 | 4 | 3 | 6 | -UNF6 |
| | 8-36 | 4,166 | 63 | 12 | 21 | 4,5 | 3,4 | 6 | -UNF8 |
| | 10-32 | 4,826 | 70 | 13 | 25 | 6 | 4,9 | 8 | -UNF10 |
| | 1/4-28 | 6,35 | 80 | 15 | 30 | 7 | 5,5 | 8 | -UNF1/4 |
| | 5/16-24 | 7,938 | 90 | 18 | 35 | 8 | 6,2 | 9 | -UNF5/16 |
| | 3/8-24 | 9,525 | 100 | 20 | 39 | 10 | 8 | 11 | -UNF3/8 |

| DIN 2184-1 2BX | D_N -P Nom | D_N мм | l_1 js16 мм | L_c мм | l_3 ± 1 мм | d_1 h9 мм | \square h12 мм | l_g мм | TiN Обозначение DP2366705 |
|----------------|-----------------|-------------|---------------------|-------------|------------------------|-------------------|------------------------|-------------|---------------------------------|
| | 7/16-20 | 11,113 | 100 | 20 | - | 8 | 6,2 | 9 | -UNF7/16 |
| | 1/2-20 | 12,7 | 100 | 21 | - | 9 | 7 | 10 | -UNF1/2 |
| | 5/8-18 | 15,875 | 100 | 21 | - | 12 | 9 | 12 | -UNF5/8 |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |

